



SPECIFICATION

	mVIS-DD-021s	mVIS-DD-028s	mVIS-DD-037s	mVIS-DD-021sp	mVIS-DD-057e	mVIS-DD-043e	mVIS-DD-024e
Dimensions (mm)	551 x 126 x 42	739 x 170 x 42	919 x 286 x 47	500 x 297 x 42	1495 x 366 x 113	1112 x 251 x 113	546 x 379 x 113
Viewable Area (mm)	535x 107	700x 131	900 x 253	477 x 268	1456 x 323	1074 x 201	518 x 324
Power Usage	26.4W	60W	25W	30W	240W	145W	145W
Reliability	50000 POH	50000 POH	50000 POH	50000 POH	50000 POH	50000 POH	50000 POH
Brightness (nits)	700 / 1000	700 / 1000	700 / 1000	700 / 1000	3000	3000	3000
Resolution (px)	1920 x 357	1920 x 357	1920 x 540	1920 x 1080	1920 x 441	1920 x 360	1920 x 1200
Mounting	Side M6 mounts	Side M6 mounts	Side M6 mounts	Side M6 mounts	Side / Rear M6 mounts	Side / Rear M6 mounts	Side / Rear M6 mounts
Operating Air Temperature	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C
Storage Temperature	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C	-20°C - 60°C
Operating Voltage	20 – 30 DCV	20 – 30 DCV	20 – 30 DCV	20 – 30 DCV	20 – 30 DCV	20 – 30 DCV	20 – 30 DCV
Aspect Ratio	16:03	16:03	16:04.5	16:09	16:03.5	16:04.5	16:10
Voltage Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Temperature Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Colours	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M
Weight	2kg	3.6Kg	7.2Kg	3.2Kg	12.9Kg	6.8Kg	5Kg