

White label Range





AD Series - White Label range - 19' Digital Passenger Display

Key Features

AD Series on board Enhanced Digital Display Screens are designed to deliver maximum value for Public Transport passengers, providers, operators and manufactures

- Specially designed for the public transport environment.
- Providing an enhanced passenger experience.
- High brightness for bright conditions
- Wide voltage supply range
- Less than 1mm Pixel Pitch V x H
- 1920px as standard Resolution
- Flexible Mounting options
- Framed or embedded (frameless) configuration
- 16,7 Million colours Show Clear high-definition passenger information
- Available with embedded or a choice of interface options
- Lightweight, can be easily accommodated.
- OEM service available

Provided in framed and frameless configuration



UK Head Office: Unit 49 Eldon Way, Paddock Wood, Kent, TN12 6BE



White label Range - Specs

19' Digital Passenger Display

| Model # | AD\$190-700WLB\$ |
|--|---|
| Display Detail | |
| DIAGONAL Display SIZE (Inch's) | 19 |
| RESOLUTION (Pixel's) | 1920 X 360 |
| BRIGHTNESS (nits) | 500-1000 |
| PIXEL PITCH VxH (mm) | 0.24825 x 0.24825 |
| CONTRAST RATIO | 1200:1 |
| ASPECT RATIO | 16:03 |
| COLOURS | 16.7M |
| RELIABILITY | 30000 POH |
| VIEWING ANGLE (V/H) | 178°/178° |
| VISIBLE AREA (mm) | 476.06 x 89.37 |
| Size & Weight Detail | |
| Embedded WIDTH (mm) | 497 |
| Embedded HBGHT (mm) | 114 |
| Embedded DEPTH (mm) | 40 |
| Embedded WBGHT (KG Approx) | 1.8 |
| Framed WIDTH (mm) | 510 |
| Framed HBGHT (mm) | 119 |
| Framed DEPTH (mm) | 48 |
| Framed WBGHT (KG Approx) | 2.2 |
| Mounting Points | M6, 2 x each on, Left Side, Right Side and top. |
| Power Detail | |
| OPERATING VOLTAGE | 22-30 Vdc on 0.5M trailing cable. |
| POWER CONSUMPTION (Approx) Monitor Version | 12W |
| Interface Detail | |
| MONITOR VERSION (m) | HDMI Socket on 0.5M trailing cable (DVI / VGA options exist |
| EMBEDED VERSION (p) | Embeded content player + HDMI in |
| EMBEDED VERSION (e) | Embeded ARM or X86 motherboard |
| Climatic Detail | |
| OPERATING TEMPERATURE | 0 Deg. C - +50 Deg. C |
| OPERATING Humidity (max) | 90% @ 30 Deg. C |
| Optional extra's | |
| Auto brightness control | none (standard) or simple or managed |
| Content control | For playing and controling Content |
| Monitoring & Reporing | For Hearbeast , status and confuguration |
| Remote control | For playing Content |
| Speakers | Custom |
| Mounting Brackets | Side or Top |
| Package | |
| 1 carton 4pcs | |
| -F | |

